

DATA SHEET

VIBRATION MONITORING SYSTEM – VC1000, TYPE – CV110mi

a) Measured Parameter	:	RMS value of Vibration Velocity (in mm/s) or Peak value of Vibration Displacement (in μm)
b) Input Signal	:	One, for Velocity Transducer types VS-068/VS-069
c) Measuring Range	:	Velocity 0-2/5/10/20/50 mm/Sec. Displacement 0-20/50/100/200/500 μm
d) Working Frequency range	:	10 Hz. to 1 kHz. $\pm 5\%$
e) Analog output	:	Isolated 4~20 mA $\pm 3\%$; $R_W \leq 500 \Omega$ 0~10 Volts $\pm 3\%$ (Connected Analog meter); $R_L \geq 100 \text{ k}\Omega$
f) Limits	:	2 (Adjustable through Potentiometer) 10....100 % Factory setting:-For LIM 1 = 60 % & LIM 2 = 80%
g) Response Delay	:	Limit 1: 1/3/10 sec. Limit 2: 1/3/10 sec.
h) Limit Relays	:	2 Nos. Contact Type: NO-C-NC
i) Self-Monitoring	:	Yes
j) Power Supply	:	230V/110V AC $\pm 10\%$, 50 Hz (Optional): 24V DC
k) Operating Condition	:	Operating Temperature Range - 30°C + 65°C Storage Temperature Range - 40°C+ 100°C Relative humidity max. 95 %, non-condensing
l) Housing Construction	:	Sturdy Alum. Housing meeting IP-65 with cable feed through fittings
m) Monitoring System Accuracy	:	<3% of measured value.